

- Dual Discrimination
- Digital or Analog Model
- Pulse Induction

-New Optional
18" Discrimination Coil



SSP-2100
ANALOG

New!



SSP-3000
DIGITAL



Optional 18" Discrimination Coil

18" Standard Coil

14" Coil

5" Coil

40" X 40" Discrimination Coil

Accurate Locators Inc.

1383 2nd Ave. Gold Hill, Oregon 97525
For Ordering (USA & Canada)

877-808-6200 ♦ 541-855-1590 ♦ 775-751-6931

International Sales: 01-541-855-1590 Fax: 775-537-6613

e-mail: accurate@accuratelocators.com



**With show rooms in
Gold Hill, OR
and
Near Las Vegas, NV**

Web site: www.accuratelocators.com

FOR MAXIMUM DEPTH

The **SSP-3000 "Digital" Discriminator** and **SSP-2100 "Analog" Discriminator** are a unique combination of a Metal Detector and a Magnetometer that work hand in hand to detect Iron, Gold and Silver Targets. Using Pulse Induction technology you can quickly discriminate between Ferrous and Non-Ferrous Metals. The Discriminators can easily detect larger objects buried up to 15 feet (4.5m) deep.

The **SSP-3000 Discriminator** comes with everything you need right out of the box.

Price \$3845.00

Digital Control Unit

40" X 40" Coil with built-in Magnetometer and carrying strap

18" Round Coil

14" Round Coil

5" Round Coil

Three Piece Arm Shaft Assembly

12V Rechargeable Battery (battery type subject to change)

12V Battery Charger (battery charger type subject to change)

Carrying Case

Instruction Manual

The **SSP-2100 Discriminator** comes with everything you need right out of the box.

Price \$3445.00

Analog Control Unit

40" X 40" Coil with Built-in Magnetometer and carrying strap

18" Round Coil

14" Round Coil

5" Round Coil (optional)

Three Piece Arm Shaft Assembly

12V Rechargeable Battery (battery type subject to change)

12V Battery Charger (battery charger type subject to change)

Carrying Case

Instruction Manual

New Optional 18" Discrimination Coil (With Magnetometer)

Price \$450.00

2 Meter Square Coil With Magnetometer

Price \$450.00

Extension Cables: 1, 2 or 3 Meter Lengths

Call for Pricing

SSP-3000 "Digital" Discriminator / SSP-2100 "Analog" Discriminator

Technical Specifications:

Working voltage: 12V. The detector turns off when the voltage becomes lower than the critical value

Continuous power consumption: min 110 mA (with no sound and light)

Maximum power consumption: 180 mA

Working Frequency: 100 Hz

Sound Range: 0.2Hz - 2.0 KHz

Battery: Rechargeable 2000mAh NiMH battery (battery type subject to change)

Charger Input: 110V AC, 60Hz

Charger Output: 17V DC (battery charger type subject to change)

Battery Charging Time (empty): max. 10 hours

Full Microprocessor Control

Automatic Ground Balance

Manual Tuner

Auto Tracking

Delay Control

Graphic Target Analyzing

Display: 122 x 32 pixel LCD module with backlight (SSP-3000) Analog Meter (SSP-2100)

All Metal/No-Motion Mode

Audio and Visual Discrimination Mode (by built-in Magnetic/Induction Sensor)

Depth Control for Maximized Detection Depth

Two Reset Controls for easy operation with both hands

Headphone Input: 1/4" Mono Jack

Possibility of using External Power Supply

Optimum Temperature Range: 0 - 50 Degrees C / 32-122 Degrees F

Weight of the control box (incl. battery): 24.69oz. (722 g)

prices subject to change without notice 6217